

General Purpose Polystyrene Resin



ACCORDING TO EU-REGURATION 2015/830 (REACH) AND GHS SDS

1. Product Identification and Company details:

Product Name : SC200/ SC201LV/ SC201LVLT/ SC202E/ SC202EF/ SC202EF/ SC203E/

SC203EL/SC206/ SC206HT

Product Type : Crystal

Product Description : Crystal Polystyrene Chemical Family (Plastic) : Thermoplastic

Manufacturing Company : Supreme Petrochem Ltd,

5th floor, Bldg. No.11, 167 Guru Hargovindji Marg, Andheri – Ghatkopar Link Road, Chakala,

Andheri (E), Mumbai – 400093, INDIA

Emergency Contact Number : 0091 22 6709 1900 Email : css@spl.co.in

Website : www.supremepetrochem.com

2. HazardsIdentification:

Eye Contact : Solid or dust may cause irritation or corneal injury due to mechanical

action.

Inhalation : Dust may cause irritation to upper respiratory tract (nose and throat).

Vapors released during thermal processing may cause respiratory

irritation.

Skin Contact : Prolonged contact is essentially nonirritating to skin. Mechanical injury

only. Under normal processing conditions, material is heated to elevated temperatures; contact with the material may cause thermal

burns.

Skin Absorption : No adverse effects anticipated by skin absorption.

Ingestion : Biologically inert. Very low toxicity if swallowed. Harmful effects not

anticipated from swallowing small amounts. May cause chocking if

swallowed.

Other effects : None

3. Composition Information:

Base Resin: CAS Registry Number: Percent by Weight:

Polystyrene 9003-53-6 90-98% Other Ingredients - $\leq 2\%$

Dose not contains any hazardous ingredients according to GHS.

4. First- aid Measures:

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of

water and seek medical advice.

If Inhaled : Move person to fresh air; if effects occur, consult a physician.

In case of skin contact : For serious burns, get medical attention. In case of skin contact with hot

polymer immediately immerse in or flush with clean, cold water.

Ingestion : No first aid procedures are required. Seek medical attention if a

significant amount is swallowed

Page 1/5



General Purpose Polystyrene Resin



5. Fire Fighting Measures:



Extinguishing Media

Fire Fighting Procedures

Special Protective Equipment for Firefighters

coat,

Unusual Fire and Explosion Hazards

Hazardous Combustion Products

: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide

fire extinguishers. Foam.

: Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires. : Wear positive-pressure self-contained breathing apparatus (SCBA)

and protective fire-fighting clothing (includes fire-fighting helmet,

trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

: Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is produced when product burns.

: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited

to Carbon dioxide, Carbon monoxide.

6. Accidental Release Measures:

Personal precautions : Sweep up to prevent slipping hazard. Avoid breathing dust. Avoid dust

formation.

Environmental precautions : Do not contaminate surface water. Prevent product from entering drains

Methods for cleaning up : Clean up promptly by sweeping or vacuum

Special advice : Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the

atmosphere in sufficient concentration. Avoid dispersal of dust in the air

(i.e., clearing dust surfaces with compressed air).

7. Handling and Storage:

Handling : Use good housekeeping for safe handling of the product. Keep out of

water sources and sewers. Spilled pellets and powders may create a slipping hazard. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by

themselves be sufficient.

Storage : Store in a cool, dry place in the original container when possible. Store

below 50°C. Keep away from moisture, excessive heat and sources of

ignition. Do not place in direct sunlight

Page 2/5



General Purpose Polystyrene Resin



8. Exposure Controls / Personal Protection:

Exposure Control : Ventilation, enclosures, or other controls may be needed to keep

airborne contaminates below exposure limits.

Personal Protective Equipment : Gloves required when handling hot material. In case of fire, wear self-

contained breathing apparatus or equivalent and full protective gear.





RespiratoryProtection

: Wear respiratory protection if ventilation is inadequate. Breathing

protection if dust is formed.



Eye Protection

: Chemical workers goggles recommended.



Ventilation

: Provide adequate ventilation when processing material at elevated

temperatures.

Other Protective Equipment : N.A.

Physical and Chemical Properties:

Physical State : Pellets /Granules

Physical Form : Solid

Color : Transparent

Vapour pressure : N/A Volatiles (By Volume) : N/A

Odour : Mild to no odour

Vapour Density (air = 1) : N/A **Boiling** point : N/A **Evaporation Rate** : None Softening point :>90°C Solubility in water (by weight) : Negligible Specific gravity (water = 1) : 1.03-1.05

Solubility in other solvents : Soluble in chlorinated solvents, aromatic solvents and ketones

10. Stability and Reactivity:

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature and

pressure.

: Avoid temperatures above 300 ℃ (572 F). Exposure to elevated Conditions to Avoid

temperatures can cause product to decompose.

Material to Avoid : Avoid solvents and oxidizing agents

: No decomposition if stored and applied as directed. Hazardous decomposition

Page 3/5



General Purpose Polystyrene Resin



11. Toxicological Information:

Toxicity of this material has not been fully assessed

Ingestion, Inhalation, Skin : Non-toxic

Skin and eye Irritation : Prolonged contact with product can result in skin and eye irritation.

Chronic effects of Over-exposure : Not a known carcinogen.

Acute toxicity : Not classified
Reproductive toxicity : Not classified
Germ cell mutagenicity : Not classified
STOT-sngle exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Animal Toxicity Data

Oral

LD 50 believed to be >5.0g/kg (rat) : Practically Non-toxic Inhalation : Not determined

Dermal

LD 50 believed to be >2.0g/kg (rabbit) : Practically Non-toxic

12. Ecological Toxicity:

Do not allow to escape into waters, waste water or soil.

Mobility : This product is insoluble and floats on water. Biodegradability : The product is not easily biodegradable. Bioaccumulation : Not expected to be bioaccumulative

Eco-toxicity : Not expected to be acutely toxic, but material in pellet or bead form may

mechanically cause adverse effects if ingested by waterfowl or aquatic

life

13. Disposal Consideration:

Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

For unused & uncontaminated product, the preferred options include sending to a licensed, permitted: Recycler, Reclaimer, Incinerator, or other thermal destruction device.

14. TransportInformation:

ADR / RID Class : Free IMDG Class : Free ICAO / IATA Class : Free

Transport in bulk according to : Not available

Marpol and IBC Code

Page 4/5



General Purpose Polystyrene Resin



15. Regulatory Information:

This material is NOT classified as dangerous for supply according to the CLP Regulation and the EU Regulation 2015/830.

This material is REACH complaint.

This material is FDA approved.

The preparation is not regulated by D.O.T.

The preparation is not Hazardous by OSHA Hazardous Communication Standard 29 CFR 1910.1200.

The preparation is on the TSCA inventory.

The preparation is not subject to specific CERLA reporting requirements.

The preparation is not subject to SARA 313 reporting requirements.

The preparation is not subject to California Safe Drinking Water and Toxic Enforcement Act (Proposition 65) reporting.

The preparation is not dangerous according to the applicable EC directive regulation.

Label not required. All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

Health: 0, Fire: 1, Reactivity: 0 (Hazard Rating: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

16. Other Information:

Additional information on this product may be obtained by calling your sales or customer service contact.

Recommended Uses and Restrictions: A polystyrene plastic - For industrial conversion as a raw material for manufacture of articles or goods. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

The information above is believed to be accurate and represents the best of our knowledge, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes